



DUCTILE IRON GROOVED FITTINGS AND COUPLINGS

MATERIAL: ASTM A 536, GRADE 65-45-12, QT 450-12 **THREADS:** BSPT & NPT (ASME 1.20.1), ISO 7-1, GB 7306 **EPDM:** RUBBER GASKET

PRESSURE RATING: 300 PSI

SIZES: 1" – 10"

SURFACE TREATMENT: Red Oxide (R), Electroplating (E), Bitumen (B), Epoxy (S), Hot Dip Galvanized (G)

 Standard Flexible Coupling	 Standard Flexible Coupling	 Standard Reducing Flexible Coupling	 Light-duty Flexible Coupling	 Heavy-duty Flexible Coupling	 Reducing Tee with Female Thread	 Reducing Tee with Female Thread	 Cross	 Reducing Cross	 Reducing Cross with Female Thread
 Standard Rigid Coupling	 Light-duty Rigid Coupling	 Angle Pad Coupling	 HDPE Coupling	 HDPE Transition Coupling	 U-Bolt Mechanical Tee	 Mechanical Tee Grooved Outlet	 Light-duty Mechanical Tee Grooved Outlet	 Mechanical Tee Threaded Outlet	 Light-duty Mechanical Tee Threaded Outlet
 90° Elbow	 90° Hydrant Elbow	 90° Drain Elbow	 90° Reducing Elbow	 Light-duty 90° Elbow	 Mechanical Cross Grooved Outlet	 Light-duty Mechanical Cross Grooved Outlet	 Mechanical Cross Threaded Outlet	 Light-duty Mechanical Cross Threaded Outlet	
 90° END-ALL Elbow	 11.25° Elbow	 22.5° Elbow	 45° Elbow	 Grooved Eccentric Reducer	 Cap	 Cap with Concentric Hole	 Cap with Eccentric Hole	 Grooved Flange	 Adaptor Flange
 Reducing tee	 Reducing tee	 Reducing Tee	 Tee	 Grooved Concentric Reducer	<p>Office: 99 RAILWAY ROAD, LAHORE, PAKISTAN Whatsapp: +1.587.700.7000 Email: agt.global@gmail.com www.AlpineSteel.com.pk Cell: 0322-4233334</p>				

